



Suspended Rod with Double Medium Support Installation Instructions

CONTENT

- (1) Straight Rod
- (2) End Caps
- (2) 36" Ceiling Support (all mounting hardware included)

HARDWARE NEEDED

- Phillips head screwdriver
- All-purpose drill
- Hacksaw (if cutting down rod)

Note: Two people are needed for this installation.

1. Measure the space of the bathroom where the Shower Rod will be placed and if needed use a hacksaw to cut the shower rod and ceiling support to desired length. (Use diagram below to assemble parts to help mark location, with O-Loop about 1 inch from the end of the rod.)
2. If not already installed, place the Caps on each end of the rod.
3. Support Bracket:
 - Position the Support Brackets at the desired location and mark for the screws.
 - Drill the holes and insert the plastic Anchors. (Please Note - depending on what material is in the ceiling, other fasteners than what is included may be required. **This rod is entirely ceiling suspended - and is only as strong as how it is installed.**)
 - Place the Support Brackets onto the ceiling and install the screws.
 - Thread the Medium Support Rods into the Brackets on each side.
4. O-Loop & Shower Rod:
 - Slide O-Loop on the Shower Rod and mark the location of the two bottom Set Screws of the O-Loop.
 - Slide the O-Loop (while attached to the Shower Rod) into the Medium Support Rod - mark the location for the top Set Screws.
 - Drill slightly smaller holes into the Shower Rod and Medium Support Rod where it was marked.
 - Place the bottom Set Screws into the O-Loop and **tighten them all the way into the Shower Rod.**
5. Lift the Shower Rod - place O-Loop into the Medium Support Rod and **tighten the top Set Screws all the way in.**

